



Overview

LEMAR Surface-Mounted 3D Round Downlight is a high-performance LED fixture designed for easy installation and a stylish look, these spotlights sit visibly on the ceiling, offering a clean, minimal aesthetic without the need for recessed mounting, Material ALU+PC. With an energy efficiency, the Surface mounted 3D Round Downlight Its minimalist design and durable housing make it suitable for residential and commercial use. Available in multiple wattages and in a range of color temperatures (3000K (Warm Light), 4000K (Cool Light) and 7000K (Day Light)) to meet diverse lighting requirements. With warranty up to 2 Years.

Electrical Specifications

Model No.	PN-18W
Power	18W
Frequency	50/60 Hz
Voltage	85-265 V

Light Specifications

Luminous Flux	1,800lm
Luminous Efficacy (rated)	100lm/W
Correlated Color Temperature (CCT)	3000K/7000K
Luminaire Light Beam Spread (Beam Angle)	180°
Color Rendering Index (CRI)	≥80

Mechanical Specifications

Housing Color	White
Material	ALU+PC
Diameter	120 mm
Ambient Temperature Range	-20°C ~ 50°C
Ingress Protection Code (IP)	IP20

Performance Warranty

Warranty	2 Years
Lifespan	30,000Hrs

APPLICATIONS

