



### Overview

Upgrade your space with the modern and energy-efficient ECO Surface-Mounted Downlight. Designed for easy installation and a stylish look, these spotlights sit visibly on the ceiling, offering a clean, minimal aesthetic without the need for recessed mounting, Material PP+PS.

Available in various sizes and color temperatures (3000K (Warm Light), 4000K (Cool Light) and 6500K (Day Light)) to suit different lighting needs.

Ideal for use in living rooms, offices, shops, retail spaces, corridors, and more. homes, ECO Spotlights deliver the perfect balance of style, simplicity, and performance.

### Electrical Specifications

Model No.	PN-22W
Power	22W
Frequency	50/60 Hz
Voltage	185-265 V

### Light Specifications

Luminous Flux	2,090lm
Luminous Efficacy (rated)	95lm/W
Correlated Color Temperature (CCT)	3000K/4000K/7000K
Luminaire Light Beam Spread (Beam Angle)	120°
Color Rendering Index (CRI)	≥80

### Mechanical Specifications

Housing Color	White
Material	PP+PS
Dimensions (D*H)	225*35 mm
Ambient Temperature Range	-20°C ~ 45°C
Ingress Protection Code (IP)	IP20

### Performance Warranty

Warranty	1 Year
Lifespan	30,000Hrs

### APPLICATIONS

