



### Overview

LEMAR Surface-Mounted Square Panel Downlight is a high-performance LED fixture designed for easy installation and a stylish look, these square spotlights sit visibly on the ceiling, offering a clean, minimal aesthetic without the need for recessed mounting, Material ALU-GLS-PS. With an energy efficiency, the Surface mounted Square Panel Downlight Its minimalist design and durable housing make it suitable for residential and commercial use. Available in multiple wattages and in a range of color temperatures (3000K (Warm Light), 6500K (Day Light)) to meet diverse lighting requirements. With warranty up to 2 Years.

### Electrical Specifications

Model No.	PN-18W
Power	18W
Frequency	50/60 Hz
Voltage	110-265 V

### Light Specifications

Luminous Flux	1,300lm
Luminous Efficacy (rated)	72lm/W
Correlated Color Temperature (CCT)	7000K/3000K
Luminaire Light Beam Spread (Beam Angle)	120°
Color Rendering Index (CRI)	≥80
Flicker Free	ON

### Mechanical Specifications

Housing Color	White
Material	SPCC+ALU+PC
Dimensions (L*W*H)	200*200*32 mm
Ambient Temperature Range	-20°C ~ 50°C
Ingress Protection Code (IP)	IP20

### Performance Warranty

Warranty	2 Years
Lifespan	30,000Hrs

### APPLICATIONS

