



### Overview

High-performance LED Bulkhead Light (Round). Available in 20W and 24W variants, designed for both indoor and outdoor use. It offers durable construction and excellent resistance to harsh environmental conditions. Suitable for general lighting in corridors, building entrances, parking areas, and industrial facilities. Available color temperatures: 3000K (Warm Light), 6500K (Day Light) and 3CCT (3000K, 4000K, 6500K). Mounting: Surface mounted – wall or ceiling. Ingress Protection: IP65 – dust and water resistant. Available in two distinctive frame colors: white and black.

### Electrical Specifications

Model No.	BH-24W
Power	24W
Frequency	50/60 Hz
Voltage	170-240 V

### Light Specifications

Luminous Flux	2,280lm
Luminous Efficacy (rated)	95lm/W
Correlated Color Temperature (CCT)	6500K
Luminaire Light Beam Spread (Beam Angle)	120°
Color Rendering Index (CRI)	≥80

### Mechanical Specifications

Housing Color	White
Material	ABS+PP
Dimensions (D*H)	280*62 mm
Ambient Temperature Range	-20°C ~ 45°C
Ingress Protection Code (IP)	IP65

### Performance Warranty

Warranty	1 Year
Lifespan	25,000Hrs

### APPLICATIONS

