



Overview

Lemar Trimless Downlight is a modern and sophisticated lighting solution featuring a frameless design that blends seamlessly into ceilings, offering a sleek and contemporary look. It is built with a high-quality aluminum body for enhanced durability and efficient heat dissipation. The integrated thermal management system ensures optimal heat dissipation, contributing to consistent performance and an extended operational lifespan. Available in 3CCT, it suits a variety of interior design styles, making it an ideal choice for homes, galleries, and offices that seek both elegant aesthetics and effective lighting.

Electrical Specifications

Model No.	PU-10W
Power	10W
Frequency	50/60 Hz
Voltage	85-265 V

Light Specifications

Luminous Flux	800lm
Luminous Efficacy (rated)	80lm/W
Correlated Color Temperature (CCT)	3000K/4000K/7000K
Luminaire Light Beam Spread (Beam Angle)	24°
Color Rendering Index (CRI)	≥80
Dimmable	NO

Mechanical Specifications

Housing Color	Black and White
Material	AL+PP
Dimensions (D*H)	85*75mm
Ambient Temperature Range	-20°C ~ 50°C
Cut Size	70mm
Ingress Protection Code (IP)	IP20

Performance Warranty

Warranty	2 Years
Lifespan	30,000Hrs

APPLICATIONS

