



FEATURES & BENEFITS

- High brightness with 140lm/W.
- Low power consumption, Eco-friendly.
- Lasts up to 50,000 hrs, 5 Years warranty.
- Easy Installation and Maintenance.
- Better heat dissipation.
- Isolated Meanwell driver.
- IP66 waterproof and dust-proof.

APPLICATIONS




LMR-FL-14

SPECIFICATIONS

ITEM NO.	Rated Power	Input Voltage	Frequency	Power Factor	Luminous Flux	Luminous Efficacy	CCT	CRI	Beam Angle	Material	Lifespan
LMR-F14-200W	200 W	85-265V	50/60 Hz	>0.9	28000 lm	140 lm/W	6000 K	>80	90°	aluminum	50000 h
LMR-F14-300W	300 W	85-265V	50/60 Hz	>0.9	42000 lm	140 lm/W	6000 K	>80	90°	aluminum	50000 h
LMR-F14-400W	400 W	85-265V	50/60 Hz	>0.9	56000 lm	140 lm/W	6000 K	>80	90°	aluminum	50000 h
LMR-F14-500W	500 W	85-265V	50/60 Hz	>0.9	70000 lm	140 lm/W	6000 K	>80	90°	aluminum	50000 h

DIMENSIONS

ITEM NO.	Rated Power	Length	Width	Height
LMR-F14-200W	200 W	400 mm	205 mm	180 mm
LMR-F14-300W	300 W	400 mm	305 mm	180 mm
LMR-F14-400W	400 W	400 mm	410 mm	180 mm
LMR-F14-500W	500 W	400 mm	510 mm	180 mm



Working Temperature	-20°C ~ 50°C
Housing Colour	GRAY
IP Grade	IP66

Made in China

