



### FEATURES & BENEFITS

- High Energy Efficiency.
- Low Power Consumption.
- Easy Installation and Maintenance.
- Multi-colors create amazing lighting effects.
- 3-5M effective lighting distance.
- Long lifespan.
- Environmentally Friendly.

### APPLICATIONS




### LMR-SPK-7W

### SPECIFICATIONS

ITEM NO.	Rated Power	Input Voltage	Frequency	Luminous Flux	Luminous Efficacy	CCT	CRI	Beam Angle	Material	Lifespan	Chip Brand
704101	7 W	85-265V	50/60 Hz	490lm	70lm/W	6500K	>80	45-55°	ALU	30000 h	Epistar
704301	7 W	85-265V	50/60 Hz	490lm	70lm/W	3000K	>80	45-55°	ALU	30000 h	Epistar
704401	7 W	85-265V	50/60 Hz	490lm	70lm/W	Red	>80	45-55°	ALU	30000 h	Epistar
704501	7 W	85-265V	50/60 Hz	490lm	70lm/W	Green	>80	45-55°	ALU	30000 h	Epistar
704601	7 W	85-265V	50/60 Hz	490lm	70lm/W	Blue	>80	45-55°	ALU	30000 h	Epistar
704701	7 W	85-265V	50/60 Hz	490lm	70lm/W	Purple	>80	45-55°	ALU	30000 h	Epistar
704801	7 W	85-265V	50/60 Hz	/	/	RGB	>80	45-55°	ALU	30000 h	Epistar

### DIMENSIONS

ITEM NO.	Rated Power	Diameter	Height
704101	7 W	75mm	245mm
704301	7 W	75mm	245mm
704401	7 W	75mm	245mm
704501	7 W	75mm	245mm
704601	7 W	75mm	245mm
704701	7 W	75mm	245mm
704801	7 W	75mm	245mm



°C	Working Temperature	-25°C ~ 45°C
Color swatch	Housing Colour	BLACK
Water droplets	IP Grade	IP65

Made in China

