



FEATURES & BENEFITS

- High Energy Efficiency.
- High Brightness.
- Low Power Consumption.
- Long lifespan.
- Easy Installation and Maintenance.
- Environmentally Friendly.

APPLICATIONS



LMR-T5

SPECIFICATIONS

ITEM NO.	Rated Power	Input Voltage	Frequency	Power Factor	Luminous Flux	Luminous Efficacy	CCT	CRI	Beam Angle	Material	Lifespan
505101	5 W	165-265 V	50/60 Hz	>0.6	380 lm	76 lm/W	6500 K	>70	120°	ALU+PS	25000 h
205301	5 W	165-265 V	50/60 Hz	>0.6	380 lm	76 lm/W	3000 K	>70	120°	ALU+PS	25000 h
206101	10 W	165-265 V	50/60 Hz	>0.6	800 lm	80 lm/W	6500 K	>70	120°	ALU+PS	25000 h
206301	10 W	165-265 V	50/60 Hz	>0.6	800 lm	80 lm/W	3000 K	>70	120°	ALU+PS	25000 h
207101	15 W	165-265 V	50/60 Hz	>0.6	1350 lm	90 lm/W	6500 K	>70	120°	ALU+PS	25000 h
207301	15 W	165-265 V	50/60 Hz	>0.6	1350 lm	90 lm/W	3000 K	>70	120°	ALU+PS	25000 h
208101	18 W	165-265 V	50/60 Hz	>0.6	1600 lm	89 lm/W	6500 K	>70	120°	ALU+PS	25000 h
208301	18 W	165-265 V	50/60 Hz	>0.6	1600 lm	89 lm/W	3000 K	>70	120°	ALU+PS	25000 h

DIMENSIONS

ITEM NO.	Rated Power	Length	Width	Height
505101	5 W	300 mm	23 mm	35 mm
205301	5 W	300 mm	23 mm	35 mm
206101	10 W	600 mm	23 mm	35 mm
206301	10 W	600 mm	23 mm <td 35 mm	
207101	15 W	900 mm	23 mm	35 mm
207301	15 W	900 mm	23 mm	35 mm
208101	18 W	1200 mm	23 mm	35 mm
208301	18 W	1200 mm	23 mm	35 mm



°C	Working Temperature	-20°C ~ 50°C
	Housing Colour	White
	IP Grade	IP20

Made in China

