



### FEATURES & BENEFITS

- High Energy Efficiency.
- High Brightness.
- Low Power Consumption.
- Long lifespan.
- Easy Installation and Maintenance.
- Environmentally Friendly.

### APPLICATIONS



### LMR-T8-20W

#### SPECIFICATIONS

ITEM NO.	Rated Power	Input Voltage	Frequency	Power Factor	Luminous Flux	Luminous Efficacy	CCT	CRI	Beam Angle	Material	Lifespan
203101	20 W	165-265 V	50/60 Hz	>0.6	2000 lm	100 lm/W	6500 K	>80	300°	GLASS	30000 h
203201	20 W	165-265 V	50/60 Hz	>0.6	2000 lm	100 lm/W	4000 K	>80	300°	GLASS	30000 h
203301	20 W	165-265 V	50/60 Hz	>0.6	2000 lm	100 lm/W	3000 K	>80	300°	GLASS	30000 h

#### DIMENSIONS

ITEM NO.	Rated Power	Length	Diameter
203101	20 W	120 mm	30 mm
203201	20 W	120 mm	30 mm
203301	20 W	120 mm	30 mm



°C	Working Temperature	-20°C ~ 50°C
Color palette icon	Housing Colour	White
Water droplets icon	IP Grade	IP20

Made in China

