



FEATURES & BENEFITS

- High Energy Efficiency.
- High Brightness.
- Low Power Consumption.
- Long lifespan.
- Easy Installation and Maintenance.
- Environmentally Friendly.

APPLICATIONS



LMR-T8-30W&36W

SPECIFICATIONS

ITEM NO.	Rated Power	Input Voltage	Frequency	Power Factor	Luminous Flux	Luminous Efficacy	CCT	CRI	Beam Angle	Material	Lifespan
203103	30 W	165-265 V	50/60 Hz	>0.6	3000 lm	100 lm/W	6500 K	>80	300°	GLASS+ALU cap	30000 h
203302	30 W	165-265 V	50/60 Hz	>0.6	3000 lm	100 lm/W	3000 K	>80	300°	GLASS+ALU cap	30000 h
203104	36 W	165-265 V	50/60 Hz	>0.6	3600 lm	100 lm/W	6500 K	>80	300°	GLASS+ALU cap	30000 h

DIMENSIONS

ITEM NO.	Rated Power	Length	Diameter
203103	30 W	1200 mm	30 mm
203302	30 W	1200 mm	30 mm
203104	36 W	1200 mm	30 mm



	Working Temperature	-20°C ~ 50°C
	Housing Colour	White
	IP Grade	IP20

Made in China

